


Cable Index

Cable No.	Conductors	Gauge	Material	Jacket Color	Voltage Rating	UL	Color Code	Outside Diameter
06	3	3/22 AWG	PVC	Orange	300 V	AWM 2464	IEC	.197" / Ø 5.0mm
07	4	4/24 AWG	PVC	Orange	300 V	AWM 2464	IEC	.197" / Ø 5.0mm
56	5	5/22 AWG	PVC	Orange	300 V	AWM 2464	IEC	.224" / Ø 5.7mm
138	9	8 x 0.34mm ² , 1 x 0.75mm ²	PUR/PVC	Black	300 V		IEC	.354" / Ø 9.0mm
139	17	16 x 0.34mm ² , 1 x 0.75mm ²	PUR/PVC	Black	300 V		IEC	.425" / Ø 10.8mm
182	4	4/22 AWG	PVC, Shielded	Orange	300 V		IEC	.217" / Ø 5.5mm
183	5	5/22 AWG	PVC, Shielded	Orange	300 V		IEC	.236" / Ø 6.0mm
184	8	8/24 AWG	PVC, Shielded	Orange	300 V		IEC	.260" / Ø 6.6mm
224	3	3/22 AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.169" / Ø 4.3mm
225	4	4/22 AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.185" / Ø 4.7mm
226	3	3/20 AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.181" / Ø 4.6mm
228	5	5/20 AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.213" / Ø 5.4mm
242	19	3X1mm ² , 16x 0.50mm ²	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.457" / Ø 11.6mm
251	4	4/22 AWG	PUR, Halogen Free, Weld Spark Proof	Orange	300 V	AWM 21198	IEC	.185" / Ø 4.7mm
256	4	3X1mm ² , 8x 0.50mm ²	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.366" / Ø 9.3mm
259	5	5 x 0.50 mm ²	PUR, Halogen Free, Weld Spark Proof	Orange	300 V	AWM 21198	IEC	.177" / Ø 4.5mm
260	3	3/22 AWG	PUR, Halogen Free, Weld Spark Proof	Orange	300 V	AWM 21198	IEC	.177" / Ø 4.5mm
265	4	4/22 AWG	PUR, Halogen Free	Grey	300 V	AWM 21198	IEC	.185" / Ø 4.7mm
268	6	6/22 AWG	PUR, Halogen Free, Weld Spark Proof	Orange	300 V	AWM 21198	IEC	.236" / Ø 6.0mm
278	8	3X1mm ² , 16x 0.50mm ²	PVC	Black	300 V	AWM 2654	IEC	.457" / Ø 11.6mm
282	8	7/24 AWG	PUR, Halogen Free, Shielded	Black	300 V	AWM 21198	IEC	.236" / Ø 6.0mm
288	4	4/22 AWG	PVC, Shielded	Black	300 V	AWM 21198	IEC	.217" / Ø 5.5mm
298	5	5/22 AWG	PUR, Halogen Free, Shielded	Black	300 V	AWM 21198	IEC	.236" / Ø 6.0mm
299	8	8/24 AWG	PUR, Halogen Free, Shielded	Black	300 V	AWM 21198	IEC	.260" / Ø 6.6mm
320	11	8x 0.34mm ² , 3x 0.75mm ²	PVC	Black	300 V	AWM 2654	IEC	.374" / Ø 9.5mm
328	7	4x 0.34mm ² , 3x 0.75mm ²	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.268" / Ø 6.8mm
330	9	6x 0.34mm ² , 3x 0.75mm ²	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.299" / Ø 7.6mm
331	11	8x 0.34mm ² , 3x 0.75mm ²	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.315" / Ø 8.0mm
332	15	3X1mm ² , 12x 0.50mm ²	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.358" / Ø 9.1mm
333	10	2x0.50mm ² , 8x 0.34mm ²	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.347" / Ø 8.8mm
337	6	6/22 AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.236" / Ø 6.0mm
343	6	6/24 AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.201" / Ø 5.1mm
344	8	8/24AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.236" / Ø 6.0mm
345	10	10/24AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.248" / Ø 6.3mm
346	12	12/24AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.252" / Ø 6.4mm
347	14	14/24AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.284" / Ø 7.2mm
348	12	2x 0.25mm ² /10x 0.14mm ²	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.236" / Ø 6.0mm
354	8	8/26 AWG	PUR, Halogen Free	Black	300 V	AWM 21198	IEC	.197" / Ø 5.0mm
357	3	3/24 AWG	PUR, Halogen Free	Grey	300 V	AWM 20233	IEC	.181" / Ø 4.6mm
358	4	4/24 AWG	PUR, Shielded	Grey	300 V		IEC	.205" / Ø 5.2mm
601	3	3/18 AWG	PVC	Yellow	300 V	AWM 2661	IEC	.290" / Ø 7.4mm
602	4	4/18 AWG	PUR	Yellow	300 V	AWM 20233	IEC	.230" / Ø 5.9mm
603	2	2/18 AWG	PVC	Yellow	300 V	AWM 2661	IEC	.290" / Ø 7.4mm
610	3	3/22 AWG	PUR	Yellow	300 V	AWM 20233	IEC	.190" / Ø 4.8mm
618	3	3/22 AWG	PVC	Yellow	300 V	AWM 2661	Automotive	.180" / Ø 4.6mm



Be Certain with Belden

Cable Index

Cable No.	Conductors	Gauge	Material	Jacket Color	Voltage Rating	UL	Color Code	Outside Diameter
619	3	3/18 AWG	CPE	Yellow	600 V	SOOW	U.S.	.370" / Ø 9.4mm
622	7	7/16 AWG	PVC	Yellow	600 V	STOW	U.S.	.560" / Ø 14.2mm
623	9	9/16 AWG	PVC	Yellow	600 V	STOW	U.S.	.660" / Ø 16.8mm
627	8	8/24 AWG	PVC	Black	300 V	AWM 2661	IEC	.250" / Ø 6.4mm
632	3	3/22 AWG	PVC	Yellow	300 V	AWM 2661	IEC	.190" / Ø 4.8mm
633	4	4/22 AWG	PVC	Yellow	300 V	AWM 2661	IEC	.190" / Ø 4.8mm
635	4	4/22 AWG	PVC, Shielded	Yellow	300 V	AWM 2661	IEC	.230" / Ø 5.9mm
637	4	4/18 AWG	TPE	Yellow	300 V	PLTC	IEC	.280" / Ø 7.1mm
643	4	4/22 AWG	TPE	Yellow	300 V	PLTC	IEC	.246" / Ø 6.3mm
644	5	5/22 AWG	PUR	Yellow	300 V	AWM 20233	IEC	.210" / Ø 5.3mm
645	3	3/18 AWG	PUR	Yellow	300 V	AWM 20233	IEC	.220" / Ø 5.6mm
649	7	7/18 AWG	PUR	Yellow	300 V	AWM 20233	U.S.	.275" / Ø 6.9mm
650	8	8/18 AWG	PUR	Yellow	300 V	AWM 20233	U.S.	.292" / Ø 7.4mm
651	9	9/18 AWG	PUR	Yellow	300 V	AWM 20233	U.S.	.313" / Ø 8.0mm
652	10	10/18 AWG	PUR	Yellow	300 V	AWM 20233	U.S.	.340" / Ø 8.6mm
654	12	12/18 AWG	PUR	Yellow	300 V	AWM 20233	U.S.	.354" / Ø 9.0mm
664	3	3/22 AWG	PUR	Yellow	300 V	AWM 20233	Automotive	.190" / Ø 4.8mm
669	19	19/18 AWG	PUR	Yellow	300 V	AWM 20233	Numeric	.489" / Ø 12.4mm
673	5	5/22 AWG	PVC	Yellow	300 V	AWM 20233	Automotive	.210" / Ø 5.3mm
674	4	4/22 AWG	PVC	Yellow	300 V	AWM 2661	Automotive	.190" / Ø 4.8mm
676	12	12/18 AWG	PUR	Yellow	300 V	AWM 20233	Numeric	.390" / Ø 9.9mm
678	2	2/16 AWG	PVC	Yellow	600 V	STOW	U.S.	.375" / Ø 9.5mm
679	4	4/22 AWG	PUR	Yellow	300 V	AWM 20233	IEC	.190" / Ø 4.8mm
688	3	3/18 AWG	PVC	Yellow	300 V	AWM 2661	Automotive	.290" / Ø 7.4mm
689	4	4/18 AWG	PVC	Yellow	300 V	AWM 2661	Automotive	.290" / Ø 7.4mm
696	6	6/16 AWG	PVC	Yellow	600 V	STOW	U.S.	.560" / Ø 14.2mm
697	6	6/18 AWG	PVC	Yellow	600 V	STOW	U.S.	.502" / Ø 12.8mm
698	8	8/16 AWG	PVC	Yellow	600 V	STOW	U.S.	.585" / Ø 14.9mm
699	10	10/16 AWG	PVC	Yellow	600 V	STOW	U.S.	.660" / Ø 16.8mm
724	12	12/16 AWG	TPE	Yellow	600 V	SE00W	U.S.	.690" / Ø 17.5mm
728	12	11/18 AWG	TPE	Yellow	600 V	SE00W	IEC	.596" / Ø 15.1mm
731	3	3/18 AWG	TPE	Yellow	300 V	PLTC	IEC	.284" / Ø 7.2mm
738	3	3/16 AWG	TPE	Yellow	600 V	SE00W	U.S.	.390" / Ø 9.9mm
739	4	4/16 AWG	TPE	Yellow	600 V	SE00W	U.S.	.415" / Ø 10.5mm
741	3	3/16 AWG	TPE	Yellow	600 V	SE00W	Automotive	.390" / Ø 9.9mm
742	5	5/16 AWG	TPE	Yellow	600 V	SE00W	Automotive	.495" / Ø 12.6mm
751	9	9/18 AWG	TPE	Yellow	300 V	PLTC	U.S.	.381" / Ø 9.68mm
755	5	5/18 AWG	TPE	Yellow	300 V	PLTC	Automotive	.333" / Ø 8.5mm
777	5	5/16 AWG	TPE	Yellow	600 V	SE00W	U.S.	.495" / Ø 12.6mm
794	5	5/18 AWG	TPE	Yellow	300 V	PLTC	IEC	.304" / Ø 7.7mm
839	4	4/16 AWG	TPE	Yellow	600 V	TC-ER	U.S.	.342" / Ø 8.69mm
877	5	5/16 AWG	TPE	Yellow	600 V	TC-ER	U.S.	.371" / Ø 9.42mm