



0905 203 000/...M

Power supply cable for installation of remote bus, 3-conductor PUR/PVC cable type.

RKU A 6-203/...M

Power supply cable for Installation Remote Bus modules, single ended with 6-pole female M23 connector, three conductor cable.

RSU 6-RKU A 6-203/0.6 M

Power supply cable for Installation Remote Bus modules, double ended with 6-pole male and female M23 connectors, three conductor cable.

M23 Male/Female connector, 3 poles	Signal	Leads
Pin 1	earth	green/yellow
Pin 2	+24 V	1
Pin 3	GND (0 V)	2
Pin 4	n.c.	
Pin 5	n.c.	
Pin 6	n.c.	



Technical Data

Conductor	3 x 1.00 mm ² bare, very finely stranded wires acc. to VDE 0295 KL6
Insulation of lead	PVC
Colors of the leads	green/yellow other wires black with numbers
Outer jacket	PUR dull, color: black Ø 6.5 mm

Electrical data

Nominal voltage	≤ 300 V
Test voltage	2 kV eff.
Resistance of conductor	≤ 19.5 Ω/km
Insulation resistance	≤ 10 MΩ/km

Mechanical data

Bending radius	min. 65 mm
Temperature range static	- 40°C(-40°F) /+90°C(+194°F)
Temperature range moved	+ 5°C(+41°F) /+90°C(+194°F)

Further details

Inflammability acc. to DIN VDE 0472-804 test type B. Resistant to oil acc. to DIN VDE 0472-803 and provides good resistance to chemicals, hydrolysis and microbes.

Part Number

0955 203 000/...M



RKU A 6-203/...M

RSU 6-RKU A 6-203/0.6 M



Standard Cable Lengths: 5 M / 10 M / 15 M

Other cable lengths or cable specifications are available upon request.