

M12-Round-Plug Connector, Single-Ended Cordsets, According to IEC 61076-2-101


RKT/LED | RKWT/LED



3- and 4-Poles (LED)


Actuator/sensor cordset, single-ended, M12, 3- and 4-poles, female straight connector with LED operation and function indicator with self-locking thread and molded cable.

RKT/LED



Actuator/sensor cordset, single-ended, M12, 3- and 4-poles, female 90° connector with LED operation and function indicator with self-locking thread and molded cable.

RKWT/LED



Pin Assignments

M12 - Male

3 poles



1 = brown
2 = n.c.
3 = blue
4 = black


4 poles




1 = brown
2 = white
3 = blue
4 = black

Wiring Diagrams


A pnp normally open = yellow-green




C npn normally open = yellow-green




F pnp normally closed/open = yellow-green



P pnp normally closed/open = yellow-yellow-green





Be Certain with Belden

M12-Round-Plug Connector, Single-Ended Cordsets, According to IEC 61076-2-101

RKT/LED | RKWT/LED

Technical Data

Environmental

| | |
|-----------------------------|--------------------------------|
| Degree of protection | IP 67 / NEMA 6P |
| Operating temperature range | -40°C (-40°F) / +90°C (+194°F) |

Mechanical

| | |
|--------------|-------------------------------|
| Molded body | TPU, translucent |
| Insert | TPU |
| Contact | CuSn, gold over nickel-plated |
| Coupling nut | CuZn, nickel-plated |
| O-ring | FKM |

Electrical

| | |
|----------------|------------|
| Current rating | 4 A |
| Voltage rating | 10-30 V DC |

Cable Specifications

| Cable No. | Outer Jacket | Gauge | Jacket Color | OD |
|-----------|--------------|-------|--------------|----------------|
| 610 | PUR | 22AWG | Yellow | .190" (4.8 mm) |
| 632 | PVC | 22AWG | Yellow | .190" (4.8 mm) |
| 633 | PVC | 22AWG | Yellow | .190" (4.8 mm) |
| 679 | PUR | 22AWG | Yellow | .190" (4.8 mm) |

| Part Number | | Pins | Outer Jacket | Standard Cable Lengths | Characteristics |
|------------------------|-------------------------|------|--------------|------------------------|-----------------|
| RKT/LED A 4-3-610/...M | RKWT/LED A 4-3-610/...M | 3 | PUR | 1M / 2 M / 5 M / 10 M | |
| RKT/LED A 4-3-632/...M | RKWT/LED A 4-3-632/...M | | PVC | 1M / 2 M / 5 M / 10 M | |
| RKT/LED C 4-3-610/...M | RKWT/LED C 4-3-610/...M | | PUR | 1M / 2 M / 5 M / 10 M | |
| RKT/LED C 4-3-632/...M | RKWT/LED C 4-3-632/...M | | PVC | 1M / 2 M / 5 M / 10 M | |
| RKT/LED F 4-633/...M | | 4 | PVC | 1M / 2 M / 5 M / 10 M | |
| RKT/LED F 4-679/...M | | | PUR | 1M / 2 M / 5 M / 10 M | |
| | RKWT/LED P 4-633/...M | | PVC | 1M / 2 M / 5 M / 10 M | |
| | RKWT/LED P 4-679/...M | | PUR | 1M / 2 M / 5 M / 10 M | |