

## 1/2"-20-Receptacle-Insert Connectors

RSE 3 U | RSE 4 U | RSE 5 U



### Male, 3-, 4-, and 5-Pole

1/2"-20 receptacle, dual keyway, 3-, 4-, and 5- pole, male insert.

RSE 3 U | RSE 4 U | RSE 5 U

### Pin Assignments

Face Views, Male / Female

**3 pole**



**4 pole**



**5 pole**





Be Certain with Belden

**1/2"-20-Receptacle-Insert Connectors**

RSE 3 U | RSE 4 U | RSE 5 U

**Technical Data**

**Environmental**

Degree of protection IP 67 / NEMA 6P  
 Operating temperature range -25°C (-13°F) / +80°C (+194°F)





**Mechanical**

Insert PA  
 Contact CuZn, pre-nickel and 0.8 microns gold-plated  
 O-ring FKM  
 Mode of connection solder connection  
 Connectable conductor solid max. 0.75 mm<sup>2</sup>  
 stranded wire max. 0.50 mm<sup>2</sup>

**Electrical**

Contact resistance ≤ 5 mΩ  
 Nominal current at 40°C 4 A  
 Nominal voltage 3-4 poles 240 V  
 5 poles 60 V encapsulated  
 Rated voltage 3-4 poles 250 V  
 5 poles 63 V  
 Test voltage 3-4 poles 2.0 kV eff. / 60 s  
 5 poles 1.5 kV eff. / 60 s  
 Insulation resistance > 10<sup>9</sup> Ω  
 Pollution degree 3

Receptacles

Part Number	Pins	Characteristics
RSE 3 U	3	 
RSE 4 U	4	 
RSE 5 U	5	