

A-Size 7/8" Mini Power 3- and 4-Pole, Male/Female Receptacle, 1/2" NPT
RSFPA | RKFPA


RSFPA | RKFPA



3- and 4-Pole


7/8" Mini Power 3- and 4-Pole, 14AWG, Male Receptacle, 1/2" NPT

RSFPA



7/8" Mini Power 3- and 4-Pole, 14AWG, Female Receptacle, 1/2" NPT


RKFPA



Pin Assignments

Face Views

3 pole
Male / Female



- 1 = black
- 2 = green/yellow
- 3 = white

4 pole
Male / Female



- 1 = black
- 2 = white
- 3 = red
- 4 = green/yellow

Be Certain with Belden

A-Size 7/8" Mini Power 3- and 4-Pole, Male/Female Receptacle, 1/2" NPT RSFPA | RKFPA

Technical Data

Environmental

Degree of protection NEMA 6P-IP68, IP67
Operating temperature range -40°C (-104°F) / +105°C (221°F)

Mechanical

Housing / Molded body PVC / Yellow
Contact carrier CuZn Alloy / Gold over Ni Plated
Shell CuZn/ Ni
Coupling nut Steel over Zn plated
Conductor insulation: PVC
Conductors 14AWG, Stranded Copper

Electrical

Voltage rating 600 V

Approvals

Wire Approvals UL-1015

Part Number	Pins	Current Rating	Standard Cable Lengths	Characteristics
RSFPA 3-1/2NPT-802/...M	3	18A	0.5M / 1M / 3M	
RSFPA 4-1/2NPT-805/...M	4	15A	0.5M / 1M / 3M	
RKFPA 3-1/2NPT-802/...M	3	18A	0.5M / 1M / 3M	
RKFPA 4-1/2NPT-805/...M	4	15A	0.5M / 1M / 3M	