

Rectangular Connectors GDM-Series GDM 2009 J grau/grey

Industrial Connecting Solutions:Rectangular Connectors:Valve Connectors (Type A -B -C):Type A:Field Attachable Valve Connectors:Valve Connectors (DIN EN 175 301-803):GDM 2009 J grau/grey https://e-catalog.hirschmann.com:443/link/57078-24228-256261-256266-256270-276215-24311-34882/en/conf/uistate

Name	GDM 2009 J grau/grey
	cable socket with central screw M 3 x 35
Delivery informations	
Availability	available
Product description	
Description	cable socket with central screw M 3 x 35
Туре	GDM 2009 J grau/grey
Order No.	931 236-106
Other standard types	black housing, Order no. 931 236-100
Number of contacts	2 + PE
Cable gland	PG 9
Conductor size	max. 1.5 mm ²
Standard	DIN EN 175 301-803-A
Housing Color	grau
Construction type Technical data	A
Pin dimensions	6.3 mm x 0.8 mm, 4.8 mm x 0.8 mm
	AC/DC 250 V
Rated voltage	
Rated current	16 A
Contact resistance	<= 4 m0hm
Type of termination	screw / cable shoe / cable eye
Suitable cables	4.5 mm to 7 mm diameter
Mounting	central nut
Material	
Contact surface material	Sn
Contact bearer material	PA
Housing material	PA
Environmental conditions	
Protection class (IEC 60529)	IP 65 (gasket necessary)
Pollution severity	3
Temperature range	-40 °C to +125 °C
Inflammability class	
Housing	94 HB
Contact bearer	94 V0
Approvals	
UR	UR
VDE	VDE
SEV	SEV
CSA	CSA
Packing unit	
Packaging unit	200 pieces
Scope of delivery and accessories	
Accessories to order separately	(NBR) flat gasket GDM 3-7, Order no. 730 801-002; (EPDM) flat gasket GDM 3-21, Order no. 731 739-004; profiled gasket GDM 3-16, Order no. 731 531-002;

Data sheet | 08/25/16 Technical Support: 1-717-217-2289 www.hirschmann.com

knurled screw GDM 3011-8, Order no. 732 574-001; stainless steel screw GDM 3011 RF-1, Order no. 734 363-001


Be Certain with Belden

Rectangular Connectors GDM-Series GDM 2009 J grau/grey

Industrial Connecting Solutions: Rectangular Connectors: Valve Connectors (Type A -B -C): Type A: Field Attachable Valve Connectors: Valve Connectors (DIN EN 175 301-803): GDM 2009 J grau/grey https://e-catalog.hirschmann.com:443/link/57078-24228-256261-256266-256270-276215-24311-34882/en/conf/uistate

Dictura

Drawing



Belden Deutschland GmbH

Im Gewerbepark 2 58579 Schalksmühle Germany

Phone: +49 7127/14-1806 E-Mail: icos-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.