

## Rectangular Connectors GDM Series

### Technical Information

| RMC 480   RMCB 480                                                                  |                                                                                                                                                           |                           |           |
|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|-----------|
|    | Description                                                                                                                                               | Order Designation         | Order No. |
|                                                                                     | Crimping flat contact (blade), suitable for GSC series connectors, cable cross-section: 0.5 to 1.5 mm² (B crimping)                                       | RMC 480                   | 731470021 |
|                                                                                     | RMC 480: Pack size 100<br>RMCB 480: 3000 items on a reel                                                                                                  | RMCB 480                  | 731468001 |
| XZC 0702                                                                            |                                                                                                                                                           |                           |           |
|    | Description                                                                                                                                               | Order Designation         | Order No. |
|                                                                                     | Crimping tool for GDM and G series contacts, color: red                                                                                                   | XZC 0702                  | 932507003 |
|                                                                                     | Cable cross-section for contact:<br>RMC 280, 0.5 to 1 mm², profile I, Order No. 731 991-021<br>RMC 480, 0.5 to 1.5 mm², profile II, Order No. 731 470-021 |                           |           |
| GDM 3-7 NBR pale brown   GDM 3-17 VMQ red   GDM 3-21 EPDM                           |                                                                                                                                                           |                           |           |
|  | Description                                                                                                                                               | Order Designation         | Order No. |
|                                                                                     | Flat gasket for GDM series rectangular connectors (type A)                                                                                                | GDM 3-7 NBR pale brown    | 730801002 |
|                                                                                     | NBR: -30 °C to +90 °C<br>VMQ (silicone): -40 °C to +125 °C<br>EPDM (LABS -free): -40 °C to +125 °C                                                        | GDM 3-17 MPQ red          | 731740002 |
|                                                                                     | Pack size: 50                                                                                                                                             | GDM 3-21 EPDM brown       | 731739004 |
|                                                                                     |                                                                                                                                                           |                           |           |
| GDM 3-16 NBR black   GDM 3-19 VMQ coral red                                         |                                                                                                                                                           |                           |           |
|  | Description                                                                                                                                               | Order Designation         | Order No. |
|                                                                                     | Profile gasket for GDM series rectangular connectors (type A)                                                                                             | GDM 3-16 NBR black        | 731531002 |
|                                                                                     | NBR: -30 °C to +90 °C<br>VMQ (silicone): -40 °C to +125 °C                                                                                                | GDM 3-19 VMQ coral red    | 731532002 |
|                                                                                     | Pack size: 50                                                                                                                                             |                           |           |
| GSE 2000-2 NBR pale brown   GSE 2000-3 EPDM                                         |                                                                                                                                                           |                           |           |
|  | Description                                                                                                                                               | Order Designation         | Order No. |
|                                                                                     | Flat gasket for appliance connector GSE... (type A)                                                                                                       | GSE 2000-2 NBR pale brown | 733973002 |
|                                                                                     | NBR: -30 °C to +90 °C<br>EPDM (silicone-free): -40 °C to +125 °C                                                                                          | GSE 2000-3 EPDM           | 733846003 |
| Pack size: 50                                                                       |                                                                                                                                                           |                           |           |
| GSAZ 35/43 NBR black   GSAZ 40/62 NBR black   GSAZ 60/120 NBR black                 |                                                                                                                                                           |                           |           |
|  | Description                                                                                                                                               | Order Designation         | Order No. |
|                                                                                     | Cylinder profile gasket for appliance male connector GSAZ                                                                                                 | GSAZ 35/43 NBR black      | 733262002 |
|                                                                                     | - 35 to 43 mm diameter                                                                                                                                    | GSAZ 40/62 NBR black      | 733264002 |
|                                                                                     | - 40 to 62 mm diameter                                                                                                                                    | GSAZ 60/120 NBR black     | 733266002 |
|                                                                                     | - 60 to 120 mm diameter (type A)                                                                                                                          |                           |           |
| NBR: -30 °C to +90 °C                                                               |                                                                                                                                                           |                           |           |
| Pack size: 50                                                                       |                                                                                                                                                           |                           |           |