

Rectangular Connectors GDM Series

Technical Information

SHK 03			
	Description	Order Designation	Order No.
	Protective cap for surface mounted male connectors as per DIN EN 175 301-803-A Pack size: 50	SHK 03	733790002
MESAP 43650			
	Description	Order Designation	Order No.
	Measuring adapter for measuring with 4 mm test leads for connectors and couplings as per DIN EN 175 301-803-A (e.g., Hirschmann GDM series), including short-circuit bridge	MESAP 43650	932818002
GDM 3011-7 GDM 3011 RF-1 GDME 3 N-7			
	Description	Order Designation	Order No.
	GDM 3011-7: central screw M3 x 35 with knurled head for GDM.../GM... series	GDM 3011-7	732488002
	GDM 3011 RF-1: stainless steel central screw M3 x 35 with Phillips combination head for GDM.../GM... series	GDM 3011 RF-1	734363001
	GDME 3 N-7: central screw M3 x 40 with knurled head for GDME... series	GDME 3 N-7	732280001
	Pack size: 50		
GMN 209-3 NBR pale brown GMN 209-12 EPDM			
	Description	Order Designation	Order No.
	Flat seal for GMN... cable socket (type B)	GMN 209-3 NBR pale brown	733273002
	NBR: -30 °C to +90 °C EPDM (silicone-free): -40 °C to +125 °C Pack size: 50	GMN 209-12 EPDM brown	733271004
GM 207-3 NBR pale brown GM 207-7 EPDM			
	Description	Order Designation	Order No.
	Flat seal for GM... cable socket (type B)	GM 207-3 NBR pale brown	731423002
	NBR: -30 °C to +90 °C EPDM (silicone-free): -40 °C to +125 °C Pack size: 50	GM 207-7 EPDM brown	731755004
GSA 20-3 NBR pale brown GSA 20-9 EPDM			
	Description	Order Designation	Order No.
	Flat seal for surface mounted male connector GSA 20 (type B)	GSA 20-3 NBR pale brown	731490002
	NBR: -30 °C to +90 °C EPDM (silicone-free): -40 °C to +125 °C Pack size: 50	GSA 20-9 EPDM brown	734033003