





LioN-Power Active I/O M12, M12 Power (L-coded), EtherNet/IP, 16DI



Type	0980 ESL 311-121
Product Description	LioN-P EtherNet/IP device, 16 digital input channels, M12 LAN connection, 4-poles, D-coded, M12 L-coded power supply, 5-poles

Diagnostic indication		
LED	Indication	Condition
1...8 A	Yellow	Channel status
1...8 DIA A	Red	Peripheral fault
1...8 B	White	Channel status
1...8 DIA B	Red	Peripheral fault
P1 Lnk/Act	Green	Connection to an Ethernet subscriber
	Green blinking	I/O device is in data exchange
	Off	No connection to another subscriber
P2 Lnk/Act	Green	Connection to an Ethernet subscriber
	Yellow blinking	I/O device is in data exchange
	Off	No connection to another subscriber
MS (Module Status)	Green	Module is ready
	Green blinking	Incorrect configuration
	Red-Green blinking	Self-test is carried out
	Red blinking	Firmware update
NS (Network Status)	Off	Device is switched off
	Green blinking	IP address present
	Green	Connection to the master is present
	Red blinking	At least one connection has timed out
	Red	IP address is already used by another device
	Red-green blinking	Self-test is carried out
U _s	Off	Device is switched off
	Green	Voltage 19V ≤ U _s ≤ 30V
U _s	Red	U _s Voltage < 19V or U _s > 30V

Bit assignment								
Bit	7	6	5	4	3	2	1	0
Input Data: 16DI								
Byte 0	4B	4A	3B	3A	2B	2A	1B	1A
Byte 1	8B	8A	7B	7A	6B	6A	5B	5A

Pin assignment		
M12 I/O port, A-coded  <ul style="list-style-type: none"> 1 = +24V 2 = In B 3 = GND 0V 4 = In A 5 = FE 	M12 Power connector, L-coded  <ul style="list-style-type: none"> 1 = +24V 2 = GND UL 3 = GND 0V 4 = +24V UL 5 = FE 	M12 EtherNet/IP, D-coded  <ul style="list-style-type: none"> 1 = TD+ 2 = RD+ 3 = TD- 4 = RD-

Part number	Order number
0980 ESL 311-121	934839001

LioN-Power Active I/O M12, M12 Power (L-coded), EtherNet/IP, 16DI

Technical Data	
Environmental Temperature	-20° C to +70° C (Operation)
Housing Material	Metal Zinc Die-cast
Contact Bearer	PA
Contact	M12 A, D-coded CuSn, Gold-plated M12 L-coded CuNi, Gold-plated
O-ring	FKM
Mechanical Data	
Weight	500 g
Protection Class (IEC 60529)	IP65, IP67, IP69K (only if mounted and locked in combination with Hirschmann/Lumberg connector)
Module Supply	
Rated Voltage	24V DC
Voltage Range	19 to 30V DC
Nominal Current	16 A
Connection Type	M12 Power, 5-poles, L-coded
Number	2
Bus-System	
Network	EtherNet/IP
Transmission Rate	10/100 Mbit/s
Address Range	0 to 255
Connection Type	M12 LAN connection, 4 poles, D-coded
Number	2
Inputs	
Number of Digital Channels	16
Type	Type 3 acc. IEC 61131-2
Sensor Type	PNP
Status Indicator	LED white or yellow per channel
Diagnostic Indicator	LED red per port
Sensor Current Supply	200 mA per port

The application of these products in harsh environments should always be checked before use.

Specifications subject to alteration.