





M12 Hybrid Single-Ended Overmolded Receptacle Cordsets, 8-Pole (Y-Coded)

Product Description		
Order Designation	RKHS 8Y	RSHS 8Y
		
Description	M12 Hybrid single-ended molded cordset with female straight receptacle, 8-pole, Y-coded, 360° shielded, chassis side thread PG9, transmits power and data (Fast Ethernet, 100 Mbit/s, Cat 5).	M12 Hybrid single-ended molded cordset with male straight receptacle, 8-pole, Y-coded, 360° shielded, chassis side thread PG9, transmits power and data (Fast Ethernet, 100 Mbit/s, Cat 5).
Type Contact	Female	Male
Number of Contacts	8 Pole (4 + 4)	
Standard	IEC 61076-2-113	
Construction Type	Y-Coded	
Technical Data		
Rated Voltage	50 V AC/DC	
Rated Current	0.5 A (data) / 6 A (power)	
Rated Impulse Voltage	0.8 kV	
Pollution Degree	3 acc. to DIN EN 60664-1 (VDE 0110-1)	
Environmental Conditions		
Protection Class (IEC 60529)	IP65, IP67, IP69K (only when mated to associated counterparts)	
Temperature Range (connector)	-40 °C to +90 °C, notice derating	
Technical Drawing		



Panel cut-out for anti-rotation protection



Panel cut-out for anti-rotation protection

L = Standard length of cable

*a = O-Ring • *b = Nut (SW18), enclosed separately • *c = O-Ring, enclosed separately • *d = anti-rotation protection

Pin Assignment
8-pin, Y-coded



































- 1 = white/orange
- 2 = orange
- 3 = white/green
- 4 = green

- 5 = blue
- 6 = white
- 7 = brown
- 8 = black

Continued Next Page

M12 Hybrid Single-Ended Overmolded Receptacle Cordsets, 8-Pole (Y-Coded)

Order Information

Order No.	Order Designation	No. of Pins	Jacket	Conductor Size	Characteristics
934925001	RSHS 8Y-922/2 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934925002	RSHS 8Y-922/5 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934925003	RSHS 8Y-922/10 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934925004	RSHS 8Y-922/15 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934925005	RSHS 8Y-922/20 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934925006	RSHS 8Y-922/25 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934926001	RKHS 8Y-922/2 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934926002	RKHS 8Y-922/5 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934926003	RKHS 8Y-922/10 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934926004	RKHS 8Y-922/15 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934926005	RKHS 8Y-922/20 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	  
934926006	RKHS 8Y-922/25 M	8	PUR, black	4x26AWG (data) and 4x0.75mm ² (power)	